

glove

Schutz/protection/protection

S3 HRO SRA - S1P HRO SRA

Sohle/semelle/outsole

Eva+Gummi/eva+caoutchouc/eva+rubber

Verarbeitung/construction/construction

Verklebt/assemblé/assembled

CE EN ISO 20345:2011

Air Mesh Futter
Doublure Air Mesh
Air mesh lining

TPU Fersenschutz
Protection du talon en TPU
TPU heel protection



Herausnehmbares gelochtes, dämpfendes EVA-Fußbett
semelle de propreté amovible en EVA antichoc
removable perforated and shock absorber EVA insole

Zwischensohle; EVA-Einlegesohle mit TPU-Schutzschicht
semelle intermédiaire en EVA avec film protecteur en TPU
EVA midsole with TPU protective film

Italienische S3 Nubuck Silk/Italienisches S1P Kalbswildleder und Mesh
S3 nubuck soie italienne/S1P veau velours italien et Mesh
S3 italian nubuck silk/S1P italian calf suede and Mesh



Passform regulär 10	Durchtrittfestigkeit k-sole/textile	Zehenkappe aluminium 200j	drop 15mm
chaussant regular 10	anti-perforation k-sole/textile	embout aluminium 200j	drop 15mm
fit regular 10	anti-perforation k-sole/textile	toe cap aluminium 200j	drop 15mm



glove requirements

Sohlenprofil aus HRO Nitrilkautschuk
caoutchouc nitrilique HRO
HRO nitrile rubber

Rutschfestigkeit SRA, Selbstreinigend
résistance au dérapage SRA autonettoyante
self-cleaning slip resistance SRA



Wasserabweisendes Obermaterial
Tige hydrofuge
Water-repellent uppers



Atmungsaktives Obermaterial
Cuir à haute respirabilité
Breathable leather uppers



Antistatisch
Chaussure antistatique
Anti-static shoes



Kohlenwasserstoffbeständige Schuhsohle
Semelle résistant aux hydrocarbures
Hydrocarbons resistant sole



Zehenkappe 200j
Embout 200j
200j toe cap



Energieaufnahme im Fersenbereich
Absorption d'énergie du talon
Heel energy absorption



Durchtrittssichere Insert
Insert antiperforation
Anti-perforation insert



Laufsohle mit Widerstand gegen Kontaktwärme
Semelle résistante à la chaleur par contact
Sole resistant to heat transmission by contact



Rutschfester sohle
Semelle antidérapantes
Slip resistant



technologies

TPU
film

Thermoplastischer Film für eine längere Lebensdauer der Zwischensohle.

Film thermoplastique pour une plus longue durée de la semelle intercalaire.

Thermoplastic film for longer life of the midsole.

EVA

Zwischensohle aus leichtem und flexiblem Material aus dem Running.

Semelle intercalaire en matériau léger et flexible provenant du secteur running.

Midsole in light, flexible material, derived from running shoes.

K SOLE

Durchtrittssichere Textilbrandsohle.

Semelle antiperforation en tissu, légère et flexible.

Perforation-proof textile insole, light and flexible.

insole active II



cod. 703.171342

works

**WOMEN
@WORK**



plus



glove

glove II low

S3 HRO SRA

cod. 701.170235

sizes 35/48



col.80013
schwarz/noir/black



col.75063
dunkelgrau/gris foncé/shadow gray

Sicherheitshalbschuh S3 aus wasserabweisendem Nubukleder Silk. Zehenkappe aus Aluminium 200J. Weite 10. Air-Mesh-Futter. Herausnehmbare gelochte Einlegesohle aus EVA mit schockabsorbierendem Einsatz. Durchtrittssicherer Einsatz K SOLE. TPU-Fersenschutz.

ZWISCHENSOHLE

aus EVA mit TPU-Schutzschicht.

SOHLENPROFIL

aus Nitrilkautschuk HRO.

Chaussure de sécurité basse S3 en Nubuck Silk hydrofuge. Embout en aluminium 200 J. Chaussant 10. Doublure Air Mesh. Semelle de propreté amovible en EVA perforé, avec insert absorbeur de chocs. Insert anti-perforation K SOLE. Protection du talon en TPU.

SEMELLE INTERCALAIRE

en EVA avec film de protection en TPU.

SEMELLE D'USURE

en caoutchouc nitrilique HRO.

S3 low-cut safety shoe in water-repellent Nubuck Silk. Aluminium 200J toe cap. Width 10. Air Mesh lining. Removable perforated EVA insole with shock absorber insert. K SOLE anti-perforation insert. TPU heel protection.

MIDSOLE

in EVA midsole with TPU film.

OUTSOLE

in HRO nitrile rubber.



col.25107
hellbraun/marron clair/camel



col.45041
dunkelrot/rouge foncé/dark red



col.30008
dunkelbraun/marron foncé/dark brown



col.75029
mond gestein/gris pierre lunaire/moon rock gray

